

New methods for fast X-ray inference

Simon Dupourqué (IRAP, Toulouse)


Lumières Workshop (2026)



Bayesian or frequentist?

$$\hat{\theta} = \min_{\theta} \mathcal{L}(\theta, X)$$


$$P(\theta | X) = \frac{P(X | \theta)}{P(X)} P(\theta)$$



Bayesian or frequentist?

$$\hat{\theta} = \min_{\theta} \mathcal{L}(\theta, X)$$

$$P(\theta | X) = \frac{P(X | \theta)}{P(X)} P(\theta)$$




This is a **philosophical** question, rather than a scientific one.

Bayesian or frequentist?

$$\hat{\theta} = \min_{\theta} \mathcal{L}(\theta, X)$$

$$P(\theta | X) = \frac{P(X | \theta)}{P(X)} P(\theta)$$



This is a **philosophical** question, rather than a scientific one.


Some methods are more robust than others, and you can use them whether you're Bayesian or frequentist

Not the Frequentist vs Bayesian debate

Adapted from Tutone & al. (2025)


**Local minima
robust approach**

**XSPEC vanilla
minimization
scheme**




NICER spectrum simulated for an absorbed blackbody and powerlaw

Garbage IN $\longleftrightarrow$ Garbage
OUT on simulated datasets




At least 20% of local
minima for a simple case

Landscape of exact inference methods




Landscape of exact inference methods




○ Methods available to X-ray community

Landscape of exact inference methods




-  Methods available to X-ray community
-  Methods I personally find funny

Landscape of X-ray Spectral fitting



XSPEC is an extremely powerful and convenient software, but 40 years of monolithic development make it hard to maintain and extend




If you want to contribute to the survey (N=18 currently)

HOW STANDARDS PROLIFERATE:

(SEE: A/C CHARGERS, CHARACTER ENCODINGS, INSTANT MESSAGING, ETC.)


SITUATION:
THERE ARE
14 COMPETING
STANDARDS.

14?! RIDICULOUS!
WE NEED TO DEVELOP
ONE UNIVERSAL STANDARD
THAT COVERS EVERYONE'S
USE CASES.






SOON:

SITUATION:
THERE ARE
15 COMPETING
STANDARDS.





JAXSPEC






JAXSPEC



A brief introduction to JAX




- A numpy-like library with
- Just-in-time compilation
 - Automatic differentiation
 - Accelerators (GPUs, TPUs)

JAX is widely use by Google, DeepMind, and grows in the machine learning community. *AlphaFold*, *Gemini* or *midjourney* are built on top of it.


Software and hardware acceleration

Rewrite the existing stack using JAX



Software and hardware acceleration

Rewrite the existing stack using JAX




Autodifferentiation

Differentiable algorithms

- Adam for minimization
- HMC/NUTS for MCMC
- Variational Inference

Software and hardware acceleration

Rewrite the existing stack using JAX



Autodifferentiation

*Transparent on
accelerators*

Differentiable algorithms

- Adam for minimization
- HMC/NUTS for MCMC
- Variational Inference


GPU/TPU acceleration



What does jaxspec bring?




- Inference on the GPU
- New algorithms
- A promise of full Python development



What does jaxspec bring?



- Inference on the GPU
- New algorithms
- A promise of full Python development



Live demo : NUTS


**THE OPERATIONS DEPICTED IN THIS FEATURE
WERE PERFORMED BY
HIGHLY TRAINED PROFESSIONALS
OPERATING UNDER CONTROLLED CONDITIONS.**

X	WARNING
DO NOT TRY THIS AT HOME	


Some performances from the jaxspec paper

- NGC 7793 ULX-4 (XMM-Newton)
- Absorbed powerlaw and blackbody emission model

Posterior predictive - PN





Increasing autocorrelation





jaxspec with **NUTS (i)** or **AIES (ii)** gives much better mixing than XSPEC with **AIES (iii)**

Some performances from the jaxspec paper




Some performances from the jaxspec paper




Time to reach convergence
 $\hat{R} < 1.01$ for
 MCMC
 samplers

- 10 order of magnitude speedup
- Equivalent results, no approximation
- **Run on equivalent material**, no GPU


Intro to Variational inference




1. **Chose a variational distribution $q(\theta)$**
e.g. "my posterior could be approximated with a multivariate Gaussian distribution"
2. **Minimize the Evidence Lower Bound**
Turn Bayesian inference into an optimisation problem. Best if performed with gradient guided minimiser (Adam)



Intro to Variational inference




1. **Chose a variational distribution $q(\theta)$**
e.g. "my posterior could be approximated with a multivariate Gaussian distribution"
2. **Minimize the Evidence Lower Bound**
Turn Bayesian inference into an optimisation problem. Best if performed with gradient guided minimiser (Adam)



Kullback–Leibler divergence


Divergence (not distance!)
between two probability
distributions

$$D_{\text{KL}}(p \parallel q) = \int p(x) \log \frac{p(x)}{q(x)}$$




Minimise the divergence between
the **variational distribution** and
the **posterior distribution**

$$D_{\text{KL}}(q(\theta) \parallel p(\theta|x))$$



Extra maths


We maximise the **Evidence
Lower Bound** (ELBO)



Kullback–Leibler divergence


Divergence (not distance!)
between two probability
distributions

$$D_{\text{KL}}(p \parallel q) = \int p(x) \log \frac{p(x)}{q(x)}$$




Minimise the divergence between
the **variational distribution** and
the **posterior distribution**

$$D_{\text{KL}}(q(\theta) \parallel p(\theta|x))$$




Extra maths

We maximise the **Evidence
Lower Bound** (ELBO)



VI for high-resolution spectroscopy




Adapted from Krapu & al. (2019)

$\tau \propto d^{0.98}$ for VI vs $\tau \propto d^{2.23}$ for NUTS

Suited for high-resolution X-ray spectroscopy

- Requires less gradient evaluation compared to NUTS
- Scales better with high number of parameters
- Fully profits from GPU acceleration, where NUTS is less efficient for multiple chains on the same device

VI for high-resolution spectroscopy



Adapted from Krapu & al. (2019)

$\tau \propto d^{0.98}$ for VI vs $\tau \propto d^{2.23}$ for NUTS



Suited for high-resolution X-ray spectroscopy

- Requires less gradient evaluation compared to NUTS
- Scales better with high number of parameters
- Fully profits from GPU acceleration, where NUTS is less efficient for multiple chains on the same device

Example : application to Hitomi

See Dupourqué & al . 2024


- 28 parameter model
- Iron complex with 3 *Hitomi* pointings on Perseus
- 10^5 steps of *adamw*
- 7 minutes on a A2 GPU




Example : application to Vela X-1

See Diez & al . 2025

- 38 parameter model + thousands of background parameters
- Powerlaw continuum, cyclotron lines, 10 keV features, emission lines ...
- 4 instruments (*XRISM/Resolve*, *NuSTAR/FPMA*, *NuSTAR/FPMB*, *XMM/Epic-PN*)
- Cross calibration
- 50 minutes inference on a H100 GPU



Example : application to Vela X-1





- Nothing here is magic, **every algorithm can fail**
- There is no single test or statistic that will give you 100% confidence
- There must be a **human in the loop** questioning the results



- Nothing here is magic, **every algorithm can fail**
- There is no single test or statistic that will give you 100% confidence
- There must be a **human in the loop** questioning the results


Conclusion

- jaxspec is in early development stage
- Yet it starts to be science ready, as it passes cross calibration tests with existing software with increasingly complex case studies
- Extending jaxspec with complex physical models (APEC, relxill) is horrendously hard
- Is surrogate modeling a good solution ?

Backup slides

Surrogate modelling in a nutshell

Example : fully ionized plasma with APEC model




- Same wild machinery with reflexion models, obscuration models etc.
- Models of this kind are usually tabulated to speed things up
- Tabulation has its own issues and scales poorly with the number of parameters

Surrogate modelling in a nutshell

Example : fully ionized plasma with APEC model

Parameters

T, Z, z, v




Continuum with
bremsstrahlung

Emission lines
with atomic DBs


Redshift and
broadenings

Extra physics I
forgot :skull:



Replace this with a neural network!

Spectrum




- Same wild machinery with reflexion models, obscuration models etc.
- Models of this kind are usually tabulated to speed things up
- Tabulation has its own issues and scales poorly with the number of parameters

Example : RTFAST

Parameters


[17 dims]



Example : RTFAST

Parameters
[17 dims]

Standard Scaling




Example : RTFAST

Emulation for X-ray reverberation spectra : check Ricketts & al. (2024)

Parameters
[17 dims]

Standard Scaling

Ensemble of 7 Dense MLP (GeLU activation)




Inverse PCA

Linear combination
of **200** fixed PCA
components

Standard
Unscaling +
Exponential
transform

- Emulation with $\mathcal{O}(3\%)$ accuracy
- 200 times faster calls
- Limited to XMM resolution



From KL to ELBO


Let's compute the KL-divergence between our variational distribution and the target posterior

$$\begin{aligned} D_{\text{KL}}(q(\theta) \parallel p(\theta|x)) &= \int_{\theta} q(\theta) \log \frac{q(\theta)}{p(\theta|x)} \\ &= \int_{\theta} q(\theta) \log \frac{q(\theta)p(x)}{p(x, \theta)} \\ &= \int_{\theta} \underbrace{q(\theta) \log q(\theta)}_{\text{Negative entropy of the variational distribution}} + \int_{\theta} \underbrace{q(\theta) \log p(x)}_{\text{Constant wrt } \theta} - \int_{\theta} \underbrace{q(\theta) \log p(x, \theta)}_{\text{Expectation of the joint probability}} \end{aligned}$$

From KL to ELBO

$$D_{\text{KL}}(q(\theta) \parallel p(\theta|x)) = \mathbb{E}_{q(\theta)} [\log q(\theta)] + \log p(x) - \mathbb{E}_{q(\theta)} [\log p(x, \theta)]$$

Rearrange the terms



$$\log p(x) = \underbrace{\mathbb{E}_{q(\theta)} [\log p(x, \theta)] - \mathbb{E}_{q(\theta)} [\log q(\theta)]}_{\mathcal{L}(q)} - D_{\text{KL}}(q(\theta) \parallel p(\theta|x))$$

$$\log p(x) = \mathcal{L}(q) - \underbrace{D_{\text{KL}}(q(\theta) \parallel p(\theta|x))}_{\text{Divergence} > 0}$$


$\log p(x) \geq \mathcal{L}(q)$ so maximising $\mathcal{L}(q)$ maximises the evidence

Bayesian inference

θ : parameters

X : observation(s)

Bayesian inference




θ : parameters

X : observation(s)

$$P(\theta | X) = \frac{P(X | \theta)}{P(X)} P(\theta)$$

Bayesian inference



θ : parameters


X : observation(s)

$$P(\theta | X) = \frac{P(X | \theta)}{P(X)} P(\theta)$$

Prior

A priori probability
of the parameters

Bayesian inference



θ : parameters

X : observation(s)

$$P(\theta | X) = \frac{P(X | \theta) P(\theta)}{P(X)}$$


Likelihood

Probability of the observation(s) given the parameters

Prior

A priori probability of the parameters

Bayesian inference



θ : parameters

X : observation(s)

Likelihood

Probability of the observation(s) given the parameters

$$P(\theta | X) = \frac{P(X | \theta) P(\theta)}{P(X)}$$


Posterior

A *posteriori* of the parameters given the observation(s)

Prior

A *priori* probability of the parameters

Bayesian inference



θ : parameters

X : observation(s)

Likelihood

Probability of the observation(s) given the parameters

$$P(\theta | X) = \frac{P(X | \theta) P(\theta)}{P(X)}$$

Posterior

A *posteriori* of the parameters given the observation(s)

Prior

A *priori* probability of the parameters

Reason why Bayesian inference is hard to perform

Reminders of X-ray spectroscopy


$$\mathcal{S}(E, \theta) = \mathcal{R} * \mathcal{M}(E, \theta)$$

Reminders of X-ray spectroscopy

$$\mathcal{S}(E, \theta) = \mathcal{R} * \mathcal{M}(E, \theta)$$

Observed data

Spectra measured by the instrument




Reminders of X-ray spectroscopy

$$S(E, \theta) = \mathcal{R} * \mathcal{M}(E, \theta)$$


Observed data

Spectra measured by the instrument



Model

Spectral model and instrumental convolution



Reminders of X-ray spectroscopy


$$S(E, \theta) = \mathcal{R} * \mathcal{M}(E, \theta)$$

Parameters

Temperature,
Abundance, Redshift...


Observed data

Spectra measured by the instrument



Model

Spectral model and instrumental convolution



Reminders of X-ray spectroscopy

$$S(E, \theta) = \mathcal{R} * \mathcal{M}(E, \theta)$$


Parameters

Temperature,
Abundance, Redshift...

Expected photons
in each channel
 $\lambda \equiv S(E, \theta)$


Observed data

Spectra measured by the instrument



Model

Spectral model and instrumental
convolution



Reminders of X-ray spectroscopy

$$S(E, \theta) = \mathcal{R} * \mathcal{M}(E, \theta)$$

Parameters


Temperature,
Abundance, Redshift...

Expected photons
in each channel

$$\lambda \equiv S(E, \theta)$$


Observed data

Spectra measured by the instrument



Model

Spectral model and instrumental
convolution



Counting process : Poisson likelihood

$$P(X = k | \theta) = \frac{\lambda^k e^{-\lambda}}{k!}$$

Turn the likelihood into
a posterior distribution


Traditional Bayesian inference

Evaluate
 $P(X | \theta)$

Traditional Bayesian inference

Sampling $\{\theta\}_i \sim P(\theta|X)$

Monte Carlo Markov Chain (HMC,
NUTS, AIES), Nested Sampling




Evaluate

$$P(X|\theta)$$

Traditional Bayesian inference

Sampling $\{\theta\}_i \sim P(\theta|X)$

Monte Carlo Markov Chain (HMC, NUTS, AIES), Nested Sampling



Evaluate
 $P(X|\theta)$

Variational $q(\theta) \simeq P(\theta|X)$

Minimize Evidence Lower Bound for a parametric and analytical approximation of the posterior distribution

