

News from the ALICE solid fixed-target setup design

June 2, 2021



Kevin Pressard

Summary

- Context of the fixed-target experiment @ ALICE
- Expected ALICE environment during run 4
- Progress in the design
 - Two valves-based design
 - Single valve-based design
- Current work and issues
- Next step


Context and reminders

- Retractable target: fine-tuning positioning from parking position (out of the pipe) to active position (4 mm away from the beam axis).
- Parasitic experiment if possible.



Possible locations of the target
(-3,5 m ; -4,7 m)

Possible ALICE layout Run 4



See September 26, 2019
Corrado's presentation

Design progress

No more valve along the beam pipe but in the tapping.

Two valves solution: valve #1 and cross #1 (where pumps and a baking system is connected) remain in the cavern, then:


- Shutting down the valve #1
- Dismounting of the assembly {valve #2, cross #2, motorization-bellow, rod, target}
- Breaking the vacuum of the assembly
- Changing the target
- Pumping and baking the assembly
- Mounting back the assembly on the cross #1
- Opening the valve #1.

Moving speed: 10 mm/s.

Accuracy: 10 μm .

Cost (motorization + bellow, crosses, valves): 25 k€.

Pumps, gauges, and the target costs are not included.



*UHVD*esign {linear motorization + bellow}. Here the bellow is compressed (stroke = 800 mm).

Primary pump, secondary pump, ionic pump and pressure gauge on each of those crosses.

Minimum distance to avoid shadow to FoCal.
 If $z_{\text{target}} = -4,7$ m from IP2, $h = 350$ mm.
 If $z_{\text{target}} = -3,5$ m from IP2, $h = 270$ mm.

LHC pipe

Vertical setup while the target is 4 mm away from the beam. Orientations of the crosses, the valves and the motorization-bellow can be modified. Rounded values to 1 mm.

Design progress

No more valve along the beam pipe but in the tapping.

One valve solution: everything remains in the cavern. Every vacuum-related job must be performed in the cavern.



Pumps and a baking system are switched on before opening the valve.

Moving speed: 10 mm/s.

Accuracy: 10 μm .

Cost (motorization + bellow, crosses, valves): 14 k€.

Pumps, gauges, and the target costs are not included.



UHVDesign {linear motorization + bellow}. Here the bellow is compressed (stroke = 500 mm).

Primary pump, secondary pump, ionic pump and pressure gauge.

Minimum distance to avoid shadow to FoCal.
 If $z_{\text{target}} = -4,7$ m from IP2, $h = 350$ mm. If
 $z_{\text{target}} = -3,5$ m from IP2, $h = 270$ mm.

LHC pipe

Vertical setup while the target is 4 mm away from the beam. Orientations of the crosses, the valve and the motorization-bellow can be modified. Rounded values to 1 mm.

Issues under investigation

- Vertical vs. horizontal integration
 - vertical, no bending

- horizontal, bending $d = \frac{m_{target}gL_{rod}^3}{3E\frac{\pi\phi_{rod}^4}{64}} + \frac{m_{rod}gL_{rod}^3}{8E\frac{\pi\phi_{rod}^4}{64}}$. If $\left\{ \begin{array}{l} m_{target} = 0.02 \text{ kg} \\ L_{rod} = 1 \text{ m} \\ \phi_{rod} = 12 \text{ mm} \\ E = 70 \text{ GPa (aluminum)} \end{array} \right. , m_{rod} = 0.31 \text{ kg and } d = 20 \text{ mm}.$

If $\phi_{rod} = 20 \text{ mm}, m_{rod} = 0.85 \text{ kg and } d = 7.1 \text{ mm}$

- Budget material optimization: crosses ($m_{cross} = 6 \text{ kg}$), valves ($m_{valve} = 9 \text{ kg}$), motor-bellows ($m_{bellow} = 13 \dots 33 \text{ kg}$)
- See Charlotte's talk for impact on FoCal
- Ultra-high vacuum environment:
 - target holder optimization (geometry, mass) and surface reduction
 - pumps dimensioning
- Alignment and positioning control
- Motor power and control
- ALICE integration: mechanical support around beam pipe and free space vs. z_{target}

Next steps

- Procedure for a target change.
- Impedance (antenna effect).
- Heat on the target to dissipate.
- Light pipe (Be? Al?).
- Aim : installation during LS3.