

Implementation of the double Penning trap mass spectrometer MLLTRAP at ALTO

Elodie Morin

September 23th, 2022

Supervised by Enrique Minaya Ramirez





Penning trap mass spectrometer (PTMS)

MLLTRAP : Two cylindrical Penning traps in a 7 T superconducting magnet

- Penning trap : superposition of high intensity magnetic field with low electrostatic field
- Application of quadrupolar field : 3 eigenmotions appear :
 - An axial motion : ν_z
 - A slow radial motion, the magnetron motion : ν_-
 - A fast radial motion, the modified cyclotron motion : ν_+
 - $\rightarrow \nu_c^2 = \nu_+^2 + \nu_-^2 + \nu_z^2; \nu_c = \nu_+ + \nu_-$
- Ion manipulation by exciting their eigenmotions
 - Isobaric purification with buffer gas cooling in preparation trap
 - Cyclotron frequency measurements in a measurement trap

$$\nu_c = \frac{\omega_c}{2\pi} = \frac{qB}{2\pi m}$$



L. S. Brown, G. Gabrielse,
Rev. Mod. Phys., 58 (1986) 233


ALTO facility at Orsay

ALTO (Accélérateur Linéaire et Tandem à Orsay)


- Ions accelerated with Tandem for High energy experiments
- Electrons accelerated in the linac :
 - Production of radioactive species by photofission in C_xU targets
 - Ionization with a surface ion source or a laser ion source (e.g. Ag case)

Observation


Production




Ag ionisation scheme




MLLTRAP@ALTO




MLLTRAP@ALTO




MLLTRAP@ALTO




MLLTRAP@ALTO



MLLTRAP@ALTO








MLLTRAP@ALTO



E. Minaya Ramirez et al.,
NIM B, 463 (2020) 315-319





M3 and M2 sections

- Transport section and control system operational
- High-voltage ion source
 - Provide alkali ions ^{133}Cs and $^{85-87}\text{Rb}$
 - Traps characterization and reference for magnetic field calibration
- RFQCB (Radiofrequency Cooler and Buncher)



M1 section and Control System


- Injection system operational
- Vacuum tube aligned with a 1.1 ± 0.1 mrad $\rightarrow$ insertion of Penning traps soon
- Magnetic probe : monitoring during measurements
- New C++ control system (CS++) developed by the Control System Framework from GSI (<https://wiki.gsi.de/CSframework/WebHome>)
 - All MLLTRAP equipment controlled by only one computer via PXIe-1082 chassis
 - PI-ICR method compatible with the new CS++



PI-ICR : Phase Imaging Ion Cyclotron Resonance

- Based on the projection of ions eigenmotions on a position-sensitive detector, a MCP delay-line

S. Eliseev et al., Appl. Phys. B, 114 (2014) 107-128




PI-ICR : Phase Imaging Ion Cyclotron Resonance

- Based on the projection of ions eigenmotions on a position-sensitive detector, a MCP delay-line

S. Eliseev et al., Appl. Phys. B, 114 (2014) 107-128


ν_{-} excitation $\rightarrow$ orbit



PI-ICR : Phase Imaging Ion Cyclotron Resonance

- Based on the projection of ions eigenmotions on a position-sensitive detector, a MCP delay-line


S. Eliseev et al., Appl. Phys. B, 114 (2014) 107-128



PI-ICR : Phase Imaging Ion Cyclotron Resonance

- Based on the projection of ions eigenmotions on a position-sensitive detector, a MCP delay-line


S. Eliseev et al., Appl. Phys. B, 114 (2014) 107-128



PI-ICR : Phase Imaging Ion Cyclotron Resonance

- Based on the projection of ions eigenmotions on a position-sensitive detector, a MCP delay-line


S. Eliseev et al., Appl. Phys. B, 114 (2014) 107-128



PI-ICR : Phase Imaging Ion Cyclotron Resonance

- Based on the projection of ions eigenmotions on a position-sensitive detector, a MCP delay-line

S. Eliseev et al., Appl. Phys. B, 114 (2014) 107-128




PI-ICR : Phase Imaging Ion Cyclotron Resonance


- Based on the projection of ions eigenmotions on a position-sensitive detector, a MCP delay-line

- $\phi_c + 2\pi(n_+ + n_-) = 2\pi\nu_c t$


S. Eliseev et al., Appl. Phys. B, 114 (2014) 107-128





ϕ_1 measurement




ϕ_2 measurement











SHIPTRAP experiment at GSI (Darmstadt, Germany)






Cryogenic gas cell to stop ions provided by SHIP

7 T superconducting magnet with two Penning traps




PI-ICR example with ^{200}At



- Isomers and contaminants resolved

Preliminary results



Excited states

Species	Litterature value (keV)	measured value (keV)
m^{196}_{Bi}	166.4 ± 2.9	171.9 ± 1.6
n^{196}_{Bi}	272 ± 3	271.7 ± 0.7
m^{198}_{Bi}	280 ± 40	173.7 ± 0.8
m^{200}_{At}	112.9 ± 2.9	118.9 ± 1.1
n^{200}_{At}	343.8 ± 3.0	375.1 ± 1.0
m^{202}_{At}	190 ± 40	144.1 ± 0.5
n^{202}_{At}	590 ± 40	414.3 ± 0.4
m^{204}_{Fr}	50 ± 4	49.6 ± 0.7
n^{204}_{Fr}	326 ± 4	330.1 ± 0.7
m^{206}_{Fr}	190 ± 40	196.1 ± 0.7
n^{206}_{Fr}	730 ± 40	548.5 ± 1.1

Only statistical uncertainties, work on systematics estimation in progress

- Center spot scattering
- Mass difference dependent shift
- Time-dependent non linear magnetic field drift
- Excitation frequency detuning (excited states or isobar studies)

Conclusion

- A new Penning trap setup is being implemented at Orsay at the ALTO facility
- Stable ion source developed for tests and magnetic field calibration to send a beam with same initial conditions as ALTO's beam
- Development and implementation of the new CS++ at MLLTRAP
- Data analysis ongoing for SHIPTRAP experiments, also allows improvements for MLLTRAP développements (PI-ICR systematics characterisation, improvement of CS++)
- Extensive study on the analysis and systematics to understand discrepancies with litterature
- In the framework of DESIR/SPIRAL2 (GANIL, Caen) : Making MLLTRAP operationnal before moving to DESIR experimental Hall




Thank you for your attention !

Backup

Nuclear physics impacts of MLLTRAP mass measurements at ALTO

Nuclear structure

- Access to binding energies → interactions inside the nucleus
- Neutron separation energies and shell gaps
- → Shell quenching for $N = 82$?




Huang et al.,
Chinese Physics C 45 (2021) 030002

Nuclear astrophysics

- Nuclear informations (including nuclear masses) are important inputs for r-process path evolution models
- $N = 82$ could be linked to $A = 130$ r-process solar abundance peak
- Non-negligible impact of Ag masses close to $N = 82$ on r-process simulations for at least 4 different scenarios

Mumpower et al,
Prog. Part. Nucl. Phys., 86 (2016)

SHIPTRAP Experimental campaign in 2021




- Main beamtime focused on Super-Heavy ^{257}Rf and ^{258}Db
- 12 days of parasitic ^{48}Ca beam, 7 days of parasitic ^{50}Ti beam, 14 days of main ^{50}Ti beam
- More than 20 isotopes above $Z = 82$ investigated, including $^{206}\text{Fr} - ^{202}\text{At} - ^{198}\text{Bi}$ decay chain
- New isomers observed and their masses precisely measured

Physical case

Study of $^{206}\text{Fr} - ^{202}\text{At} - ^{198}\text{Bi}$ α decay chain

- Odd-Z and odd-N, $Z > 82$ neutron-deficient nuclei
- Main motivation in this region of nuclear chart : shape coexistence, need of excitation energies for calculations
- For $^{206}\text{Fr} - ^{202}\text{At} - ^{198}\text{Bi}$:
 - Hyperfine structure and isotopic shift determined for ground and excited states
 - But excitation energies not directly accessed so far
- Direct mass measurement performed using PI-ICR methods at SHIPTRAP



M. Huyse, Phys. Rev. C, 46 (1992) 1209


J. Uusitalo, Phys. Rev. C, 71 (2005) 024206

K. M. Lynch, Phys. Rev. C, 93 (2016) 014319

Ion manipulation


Manipulation of the eigenmotions performed by dipolar and quadrupolar excitation applied on the segmented ring electrode

● Dipolar excitation :



Applied at eigen frequencies, modifies the amplitude of the eigenmotions


● Quadrupolar excitation :







Applied at the sum of eigenfrequencies, couples the eigenmotions and converts one eigenmotion to the other

Data taking

- Alternation of data acquisition on an interest ion, center spots and a reference ion
- The way data are taken influences the way the data will be analysed :




- Reference phases measurements
- Center spot measurements
- Magnetron phases measurements
- Reduced cyclotron phase measurements




(185 ms accumulation time)

Center spot scattering



Position of the center moves from one run to another
Estimation of uncertainties with standard deviation

Mass difference dependent shift




Courtesy to M. J. Gutiérrez

$$\bullet R_{lit} = \frac{\nu_{c,t}^{exp} - \Delta\nu}{\nu_{c,r}^{exp} - \Delta\nu}$$

- Imperfection of the electric-quadrupole field
- Misalignment of electrostatic trapping field with respect to magnetic field

Time-dependent non-linear magnetic fields drift



Thesis of O. Kaleja, JGU Mainz

- Magnetic field intensity of such superconducting magnets drifts over years
- This drift can be linearly estimated by a campaign of equal time spaced measurements on a reference ion during a couple of days